

ImagePerfect™ 2563 Monomeric Print Film carries the industry's best value to performance ratio in the Short Term film segment. The highly opaque and ink receptive film looks and prints like a premium product. The solvent pressure sensitive adhesive works on a wide range of signage substrates to provide consistent graphic anchorage. The moisture/heat resistant Double Side PE coated release liner is designed to keep the film laying flat through the large-format inkjet printing process. The film is compatible with Eco-Solvent, Solvent, UV and Latex inks.

## IP 2563

This monomeric vinyl has been specifically designed for lay flat printing with all Eco-Solvent, Solvent, and Latex inks.

It should be used only on flat surface applications and is intended for indoor and outdoor use.

Laminate: IP 2567 or 2568

## Specifications

Description	Monomeric printable PVC Film
Colour	White
Thickness	100 micron
Weight	N/A
Adhesive	Solvent based acrylic, permanent
Adhesive Strength	>3 (lbf/in) @ 24 hours
Release Paper	Double-side PE-Coated silicone paper, 140g/m <sup>2</sup>
Temperature Range	-10°C to +50°C
Durability (Unprinted)	Up to 3 Years
Flame Retardancy	N/A
Shelf Life	18 months, 20°C / 50% humidity
Recommendation	For optimal print quality please ensure that the media feed adjustment has been completed

© October 2016 Spandex Group. Technical specifications are subject to change without prior notice. All trademarks mentioned are the property of their respective owners. Output may vary depending on the type of print data/file, application, media, environmental conditions, print speed or other variables.

Information on physical and chemical characteristics is based upon tests we believe to be reliable. The values listed herein are typical values and are not for use in specifications. They are intended only as a source of information and are given without guarantee and do not constitute a warranty. Purchasers should independently determine, prior to use, the suitability of this material for its specific use. All technical data are subject to change.

The durability is based on mid European exposure conditions. Actual performance life will depend on substrate preparation, exposure conditions and maintenance of the graphics. For instance, exterior performance will be decreased in the case of signs facing south, in areas of long high temperature exposure such as southern European countries, in industrially polluted areas or in areas of high altitude. Also, for horizontal applications, exterior performance will decrease.

The print media should be completely dry before further processing, such as cutting, laminating, varnishing or application, or the residual solvents can otherwise change the specific feature of the product. To ensure the best possible outcome, the match-component ImagePerfect™ profile should be used with the relevant ImagePerfect™ media.